

ZRY-MT4AB1 controller manual

【1. Model】 ZRY-MT4AB1

【2. Specifications

2.1 Input: DC12V/24V

2.2 Lamp strip output: less than 5.0A

2.3 Defogging Output: Controlled by built-in power supply relay (less than 2.0A)

2.4 The operating temperature of this product should be below 70°C (working ambient temperature + product temperature rise).

【3. Operation instructions】.

4.1 Ship type switch toggle switch defogging.

4.2 Briefly press the middle button on the encoder switch to turn on the light, then briefly press again for 5 seconds to switch color temperature (cool light > neutral light > warm light > cycle), exceeding 5

After a few seconds, press briefly again to turn off the light, no longer switching color temperature. After 1 hour of on, the light will automatically turn off.

4.3 Rotate the encoder for brightness: turn left to dim it, right to brighten. After dimming, briefly press the middle button for 5 seconds to switch color temperature, then resume after 5 seconds

Briefly press to turn off the light.

[4. Notes]

5.1 Power under neutral light is the same as under cool or warm light.

5.2 The brightness, color temperature, and switch status of the light strip have power-off memory functions.

5.3 Encoder Wire: 400mm.

5.4 Ship type switch wire length is 1200mm

[5. Structural Dimension Drawings]

Unit: mm

